



Pin Family	SBT	SBT	SBT	SBT	SBT	SBT
Part Number	P-P185A	P-P184A	P-P196A	P-P150A	P-P151A	P-P152A
Minimum Pitch (mm)	0.4	0.4	0.5	0.5	1.0	1.0
Pin Type	BGA	LGA	BGA	LGA	BGA	LGA
Length (mm)	3.81	2.9	3.86	2.95	5.69	4.45
DUT Side Tip Shape	V Shape	Radius Cone	V Shape	Radius Cone	Notched V	Radius Cone
DUT Side Tip Dimension (mm)	0.14	0.12	0.2	0.06	0.54	0.1
PCB Side Tip Shape	Radius Cone	Radius Cone	Radius Cone	Radius Cone	Radius Cone	Radius Cone
PCB Side Tip Dimension (mm)	0.12	0.12	0.04	0.06	0.1	0.1
DUT Side Travel (mm)	0.5	0.3	0.33	0.33	0.6	0.6
PCB Side Travel (mm)	0.1	0.1	0.1	0.1	0.1	0.1
Force (g)	17	14.5	30	30	19	19
Cres (mOhms)	< 50	< 50	< 30	< 30	< 15	< 15
CCC @ ambient (Amps)	1.8	1.8	4.0	6.0	8.0	8.0
Bandwidth (GHz @ -1dB)	20.5 - 31.7	20.5 - 31.7	5.2 - 15.7	5.2 - 15.7	14.1 - 21.9	14.1 - 21.9
Self inductance (nH)	0.98	0.98	0.88	0.88	0.93	0.93
Temperature (deg C)	-55 to +180C	-55 to +180C	-55 to +180C	-55 to +180C	-55 to +180C	-55 to +180C
Insertion Cycles	50K	50K	500K	500K	500K	500K

\* 0.4mm/0.5mm pitch SBT pins are used in 0.65mm and 0.8mm pitch applications